



CS1200 Tank Alarm

This alarm system monitors liquid levels in lift pump chambers, sump pump basins, holding tanks, sewage, agricultural, and other water applications.

The CS1200 alarm system can serve as a high or low level alarm depending on the float switch model used.

The alarm horn sounds when a potentially threatening liquid level condition occurs. The horn can be turned off, but the alarm light remains on until the condition is remedied. Once the condition is cleared, the alarm will automatically reset.

A green "Power On" light indicates 120 VAC primary power to the alarm. Low battery chirp feature indicates when battery should be replaced.

UL Listed. CSA Certified. Three-Year Limited Warranty.



FEATURES

- NEMA 1 enclosure, designed for ease of installation, rated for indoor use.
- Automatic alarm reset.
- Red "alarm" light and green "power on" light, alarm "test" switch, and horn "silence" switch.
- Alarm horn sounds at 87 decibels at 10 feet (3 meters).
- Can be used with any UL Listed / Recognized switching mechanism rated to include 1 amp, 9 VDC load.
- If primary power fails, the alarm system continues to work due to battery backup feature (battery not included).
- Complete package includes standard SJE SignalMaster® control switch with 15 feet (4.57 meters) of cable (other lengths available) and mounting clamp.
- Switching mechanism operates on low voltage and is isolated from the power line to reduce the possibility of shock.
- Low battery chirp.
- Easy access battery compartment.
- External terminal block for easy float switch installation.

OPTIONS

When ordered with the alarm, this system is available with:

- Alternate float switch models for high or low level warning.
- Auxiliary dry normally open and normally closed contacts (CS1200 alarm with auxiliary contacts included is CSA certified only).
- Splice kit.

ORDERING

Please call factory for available models and list pricing.

SPECIFICATIONS

Voltage for 120 VAC Model:

Primary: 120 VAC, 60 Hz, 2.4 watts max. (alarm condition)

Secondary: 9 VDC

Battery backup power: 9 VDC

Alarm Enclosure: 6 x 4 x 2.25 inch (15.24 x 10.16 x 5.71 cm), NEMA 1 plastic.

Alarm Horn: 87 decibels at 10 feet (3 m)

Power Cord: 6 foot (1.8 m)

Float Switch Connection Terminal:

For float switch connection only.
Do not apply power. (Voltage across terminals is 8-9 VDC).

Float Switch: SJE SignalMaster® control switch with mounting clamp

Cable: 15 feet (4.57 meters), flexible 18 gauge, 2 conductor (UL) SJOW, water-resistant (CPE)

Float: 2.74 inch diameter x 4.83 inch long (7.0 cm x 12.3 cm), high impact, corrosion resistant polypropylene housing for use in sewage and water up to 140oF (60oC)

Auxiliary Alarm Contacts (optional): (CSA certified only unit)

Voltage: 120 VAC

Current: 5 amps maximum N/O
3 amps maximum N/C